

Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: illbruck PU010

· MSDS code: A-I-PU010

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Sealant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Productie B.V. Vlietskade 1032, 4241 WC Arkel

T: +31 (0) 183568000, F: +31 (0) 183568100

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely	[,] flammable aerosol	l. Pressurised	l container: M	ay burst if h	neated.

fficulties if inhaled.
eated exposure.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Contains:

diphenylmethanediisocyanate, isomers and homologues

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P284 In case of inadequate ventilation wear respiratory protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Supplemental information:

EUH204 Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Active substance with propellant

· Dangerous components:		
CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues	30- <50%
	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	
911-815-4	tris(2-chloro-1-methylethyl)phosphate	10- <20%
Reg.nr.: 01-2119486772-26-xxxx	Acute Tox. 4, H302	
	(Cor	td. on page 3)

– GB



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

	(Co	ntd. of page 2)
CAS: 115-10-6	dimethyl ether	5- <10%
EINECS: 204-065-8	Flam. Gas 1, H220; Press. Gas C, H280]
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 25791-96-2	Glycerol, propoxylated	5- <10%
NLP: 500-044-5	Acute Tox. 4, H302]
CAS: 75-28-5	isobutane	1- <5%
EINECS: 200-857-2	Flam. Gas 1, H220; Press. Gas C, H280	1
Reg.nr.: 01-2119485395-27-xxxx		
926-564-6	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol,	1- <5%
Reg.nr.: 01-2119971810-36-xxxx	L	
	Acute Tox. 4, H302	
CAS: 74-98-6	propane	1- <5%
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas C, H280]
Reg.nr.: 01-2119486944-21-xxxx		

· Additional information:

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Carbon dioxide

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

(Contd. on page 4)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

(Contd. of page 3)

Carbon dioxide

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from water.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

(Contd. of page 4)

· 8.1 Control parameters

· Ingre	· Ingredients with limit values that require monitoring at the workplace:		
9016-	9016-87-9 diphenylmethanediisocyanate, isomers and homologues		
WEL	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO		
115-1	0-6 dimethyl ether		
WEL	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

· Eye protection:



Tightly sealed goggles

Body protection: Protective work clothing

- 66

(Contd. on page 6)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

Melting point/Melting range:
 Boiling point/Boiling range:
 Not applicable, as aerosol.
 Not applicable, as aerosol.

· Flash point: -97 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· **Self-igniting:** Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: 3.0 Vol % **Upper:** 18.6 Vol %

· Vapour pressure at 20 °C: 5200 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 1.03 g/cm³
 Not determined.
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC (EU) 180.1 g/l **VOC (EC)** 17.50 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 7)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

(Contd. of page 6)

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50	· LD/LC50 values relevant for classification:				
9016-87-9	9016-87-9 diphenylmethanediisocyanate, isomers and homologues				
Oral	LD50	> 10000 mg/kg (rat)			
Dermal	LD50	> 10000 mg/kg (rabbit)			
Inhalative	LC50/4 h	0.493 mg/L (rat)			
tris(2-chlo	tris(2-chloro-1-methylethyl)phosphate				
Oral	LD50	632 mg/kg (rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic tox	· Aquatic toxicity:			
9016-87-9 d	liphenylmethanediisocyanate, isomers and homologues			
LC0/96 h	> 1000 mg/L (brachydanio rerio)			
EC50/24 h	> 1000 mg/L (daphnia magna)			
·		(Contd on nogo 0)		

(Contd. on page 8)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

	(Contd. of page 7)
NOEC/21 d	> 10 mg/L (daphnia magna)
tris(2-chlor	o-1-methylethyl)phosphate
LC50/96 h	51 mg/L (pimephales promelas)
EC50/48 h	131 mg/L (daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- Other information: The product is not easily biodegradable.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
16 05 05	gases in pressure containers other than those mentioned in 16 05 04	
15 01 04	metallic packaging	
17 06 04	insulation materials other than those mentioned in 17 06 01 and 17 06 03	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
· ADR	1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
		(Contd. on page 9)

(Contd. on page 9)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

(Contd. of page 8) · 14.3 Transport hazard class(es) · ADR 2 5F Gases. · Class · Label 2.1 · IMDG, IATA · Class 2.1 · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D.S-U · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Transport category (Contd. on page 10)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010	Trade	name:	illbruck	PU010
----------------------------	-------	-------	----------	-------

 Tunnel restriction code Remarks: Special provisions: 190, 327, 344, 625 (3.3) Special provisions for carriage: V14 (7.2.4); 0 CV12 (7.5.11); S2 (8.5) IMDG Limited quantities (LQ) Excepted quantities (EQ) Remarks: Special provisions: 63, 190, 277, 327, 344, (3.3) IATA Remarks: Special provisions: A145, A167, A802 (4.4) 		
- Special provisions: 190, 327, 344, 625 (3.3) - Special provisions for carriage: V14 (7.2.4); 0 CV12 (7.5.11); S2 (8.5) - IMDG - Limited quantities (LQ) - Excepted quantities (EQ) - Remarks: - Special provisions: 190, 327, 344, 625 (3.3) - CV12 (7.5.11); S2 (8.5) - IL - Code: E0 - Not permitted as Excepted Quantity - Special provisions: 63, 190, 277, 327, 344, (3.3) - IATA - Remarks: - Special provisions: A145, A167, A802 (4.4)		(Contd. of page 9)
 Limited quantities (LQ) Excepted quantities (EQ) Remarks: IATA Remarks: Special provisions: A145, A167, A802 (4.4) 		- Special provisions: 190, 327, 344, 625 (3.3) - Special provisions for carriage: V14 (7.2.4); CV9,
• Remarks: - Special provisions: A145, A167, A802 (4.4)	Limited quantities (LQ)Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity - Special provisions: 63, 190, 277, 327, 344, 959
LINE WAR and L. Daniel Carella		- Special provisions: A145, A167, A802 (4.4)
· UN 1950 AEROSOLS, 2.1	· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"CHIP" SI 2009 No.716.

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 28, 29
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 11)



Printing date 31.05.2016 Version number 7 Revision: 31.05.2016

Trade name: illbruck PU010

(Contd. of page 10)

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· * Data compared to the previous version altered.

GB